







### **FASTRAK REEL RACKS**

Based on the popular FastRak Bulk shelving, these rugged Reel Racks are super strong and highly versatile. Heavy duty uprights are completely welded. Beams attach quickly to uprights using popular "tear drop" design and can be adjusted in 11/2" increments. Beams also feature a built-in locking clip for added safety. Free standing "Starter Units" include 2 uprights, 3 beams and 3 rods (36" tall units include two rods). Create a row of racks by purchasing "Add-On" units. Customize your rack by purchasing additional rods (1 per level) and brackets (2 brackets are required per level). 1" diameter rod can support up to 350 lbs. per level. Unit capacity is 4,000 lbs.

	Starter Units	Add-On Units		
WxD	Model Number	Model Number		
	3' High Units			
24" x 18"	FRS-2418-036	FRT-2418-036		
36" x 18"	FRS-3618-036	FRT-3618-036		
48" x 18"	FRS-4818-036	FRT-4818-036		
	8' High Units			
24" x 24"	FRS-2424-096	FRT-2424-096		
36" x 24"	FRS-3624-096	FRT-3624-096		
48" x 24"	FRS-4824-096	FRT-4824-096		
24" x 36"	FRS-2436-096	FRT-2436-096		
36" x 36"	FRS-3636-096	FRT-3636-096		
48" x 36"	FRS-4836-096	FRT-4836-096		

	Starter Units	Add-On Units		
WxD	Model Number	Model Number		
	6' High Units			
24" x 24"	FRS-2424-072	FRT-2424-072		
36" x 24"	FRS-3624-072	FRT-3624-072		
48" x 24"	FRS-4824-072	FRT-4824-072		
	10' High Units			
	10′ Hi	gh Units		
24" x 24"	10' Hi	gh Units FRT-2424-120		
24" x 24" 36" x 24"				
~	FRS-2424-120	FRT-2424-120		
36" x 24"	FRS-2424-120 FRS-3624-120	FRT-2424-120 FRT-3624-120		
36" x 24" 48" x 24"	FRS-2424-120 FRS-3624-120 FRS-4824-120	FRT-2424-120 FRT-3624-120 FRT-4824-120		



Ex	ctra Rods	Extra I	Brackets	
Size	Model Number	Desc.	Model Number	
	215-CR01024			
36" Bar	215-CR01036	Right Bracket	215-CRBR01	
48" Bar	215-CR01048			



# **FASTRAK TIRE STORAGE SHELVING**

The FastRak design makes these extra heavy duty units perfect for storing today's larger tires. Recommended for tires that accommodate 16" and larger rims. 48"W, 72"W, and 96"W units accommodate 6, 9, and 12 tires (estimated) per level respectively. All units are 18" deep. Units feature a newly designed upright that can be "knocked down" for easier shipment. Optional deluxe foot plates and concrete wedge anchors are available for added safety.

		Starter Units	Add-On Units		Starter Units	Add-On Units
WxD	# of Levels	Model Number	Model Number	# of Levels	Model Number	Model Number
		8' High Units		10' High Units		
48" x 18"	3	K33S-4818096	K33T-4818096	4	K34S-4818120	K34T-4818120
72" x 18"	3	K33S-7218096	K33T-7218096	4	K34S-7218120	K34T-7218120
96" x 18"	3	K33S-9618096	K33T-9618096	4	K34S-9618120	K34T-9618120



Optional Deluxe	Footplate	Concrete Wedg	ge Anchor
Model Number	Weight	Model Number	Weight
CUCF01	1.0	235-FA01	0.1

## STOCK RACKS



#### Vertical Stock Rack - Model# 235-SRV1

High strength tubular steel arms extend 8" from the frame. Pan shelves are spaced 21" apart. The unit base is 36" wide x 24" deep. Unit is 84" high and has a capacity of 3,000 lbs. Unit weight is 80 lbs. Finish: Powder Coated Gray

#### Horizontal Stock Rack - Model# 235-SRH1

This unit is 84" high x 22" square at bottom and is tapered to  $4^{1/2"}$  square at the top. Angled steel arms are spaced every  $8^{1/2"}$  and extend 8" from uprights. Capacity per pair of arms is 100 lbs. Unit weight is 60 lbs. Finish: Powder Coated Gray



Two 235-SRH1 shown



2180 S Constitution Blvd, Salt Lake City, UT 84119